



**Disposition der Rohlf-Orgel
Mauritiuskirche Altbulach, op. 158 / Bj. 2004**

Manual, C - g³

| | |
|-----------------|-----------------------------|
| 1 Gedackt 8' | Fichtenholz / Birne |
| 2 Principal 4' | 82% Zinn, Prospekt |
| 3 Rohrflöte 4' | 98% Blei, (C - H ohne Rohr) |
| 4 Nasard 2 2/3' | 98% Blei |
| 5 Octave 2' | 52% Zinn |

Kanaltremulant

Pedal, C - f'

| | |
|----------------|-----------------------------|
| 6 Subbass 16' | Eichenholz, ab c' offen |
| 7 Octavbass 8' | Eichenholz, aus Subbass 16' |

Pedalkoppel



| | | | | | | | | | | | | | |
|------------------------|-----------|-----------|-----|-----------|------|-----------|-----|-----------|-------|----------|-------|----------|-------|
| Temperatur | Centwerte | C | 0 | Cs | 92,5 | D | 194 | Ds | 295,5 | E | 392,5 | F | 498,5 |
| nach Werckmeister 1691 | | Fs | 591 | G | 697 | Gs | 794 | A | 891 | B | 997 | H | 1094 |

Winddruck 52 mmWS

Einweihung am 10. Oktober 2004